

**Serie | 4, Wall mounted hoods, 90 cm,
Stainless steel
DWB97DM50B**

B



Box-design hood: performance and matching kitchen design bundled in one hood.

- **Push buttons:** simply modify the desired power level settings with mechanic control.
- **Extraction rate:** at 710 m³/h, it quickly ensures optimal kitchen air quality
- Extremely quiet at a mere 65 dB.

Technical Data

Typology :	Chimney
Approval certificates :	CE, G-Mark, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	583-912/583-1022
Height of product, without chimney (mm) :	53
Net weight (kg) :	13.471
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	454
Boost position output recirculating (m ³ /h) :	379.0
Boost position air extraction (m ³ /h) :	739
Number of lights :	2
Noise level (dB) :	65
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Optional accessories :	DHZ1225, DHZ1235, DHZ9550, DHZ9551, DSZ5201, DSZ6200, DWZ0DX0A0, DWZ0DX0U0, DWZ0XX0I0, DWZ0XX0J0, DZZ0XX0P0, DWZ1FX5C6, DZZ1XX1B6, DWZ1DX1I6, DWZ1FX5D1
Type of lamps used :	LED
Grease filter type :	Multilayer cassette
Connection Rating (W) :	255
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, G-Mark, VDE
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	19.29 x 25.59 x 40.55
Net weight (lbs) :	30
Gross weight (lbs) :	42
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	635-1075 MM x 900.0 x 500.0
Dimensions of the packed product (HxWxD) (mm) :	490 x 650 x 1030
Net weight (kg) :	13.471
Gross weight (kg) :	19.2



**Serie | 4, Wall mounted hoods, 90 cm,
Stainless steel
DWB97DM50B**

**Box-design hood: performance and matching
kitchen design bundled in one hood.**

Design

- Wall hood
- Touch control

Key Functions

- 4 fan speed settings (three plus intense) via Touch control
- 4 fan speed settings (three plus intense)
- Noise min./max. Normal Level: 52/65 dB
- Energy Efficiency Class: B
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 65 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)

Operation and power

- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 90 cm x 50 cm
- Suitable for ducted or recirculating operation only
- Recirculation kit or clean air kit
- 90 cm Wall-mounted
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

** In accordance with the EU-Regulation No 65/2014*