

BenQ MU641 WUXGA Wireless Meeting Room projector

Lens Control	Manual Zoom and Focus
Projection System	DLP Single 0.48" WUXGA
DMD Chip	DC3 DMD Chip
Native Resolution	1920 x1200 pixels
Brightness	4000 ANSI Lumens
Contrast Ratio	10,000:1
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Throw Ratio	1.47~1.76
Projection Size	30" ~ 300"
Zoom Ratio	1.2x
Keystone Adjustment	Vertical: ± 40 degrees
Projection Offset	100% \pm 2.5%
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920X1200)
Horizontal Frequency	15~102KHz
Vertical Scan Rate	23 ~ 120 Hz

Dimensions(W x H x D)	353 *135 * 272 mm
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	3.7 kg
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish / Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnamese (30 Languages)
Security	Security Bar, Kensington Security Slot
Power Consumption	Max 335W. Normal 300W. Eco 220W.
Light Source	Lamp
Light Source Life	4000/10000/8000/15000 hours(Normal/Eco/SmartEco/Lamp save mode)
Interface	HDMI-1 x1 HDMI-2/MHL x1 USB TypeA(1.5A power) x1 USB Type min B(For Page up/down and FW upgrade) x1 Computer In-1 (D-sub 15pin, Female) x1 Monitor out (D-sub 15pin,Female) x1 RS232 In (D-sub 9pin, male) x1 Composite Video(RCA) x1 S-Video x1 Audio in(mini jack) x1 Audio out(mini jack) x1 IR Receiver(Front+Rear) x2
Noise Level	33/29 dBA
Built in Speaker	2W
Accessories (Standard)	Remote control (5J.JGV06.001) AAA Batteryx2 Power Cord (by region) VGA cable Warranty Card (by region) QSG (4J.JHH01.001)

	User Manual CD (5B.JHH01.001)
Accessories (Optional)	<p>Spare Lamp Kit (5J.JHH05.001)</p> <p>3D Glasses (5J.J9H25.002)</p> <p>Wireless Dongle - QCast Mirror QP20* (5A.JH328.10X)</p> <p>Wireless Dongle - QCast QP01 (5J.JCK28.X01)</p> <p>Wireless Kit - InstaShow WDC10 (5J.JF828.X30)</p> <p>Ceiling mount</p>
Operating Temperature	0 ~ 40°C
Environmental Notice	<p>*LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.</p> <p>* The Contrast is measure by Full On Full Off standard.</p> <p>* QCast Mirror Transmission quality depends on the Wi-Fi environment and the mirror function's compatibility with different mobile devices.</p>
Dimensions (W x H x D) & Weight	Optional Wireless presentation
Power Supply	100 ~ 240V AC
Standby Power Consumption	Normal < 0.5Watts.