

INDUSTRIAL DRY CLEANING EQUIPMENT

INDUSTRIAL DRY CLEANING MACHINE (M.T.O.)

- Front Loading, open pocket Auto Timed, & Auto Reverse, & Forwarding through micro controlled Base cyclic Time, Auto filtration with low spin extract.
- Ideal for petrol solvent (MTO) cleaning in the most efficient and economical.
- Manner with high quality results.
- Stainless steel Inner basket & mild steel outer casing.
- Large loading & Unloading door outer body duly painted.



Model	Capacity Dry Wt. Per Charge	Basket Size Volume	Dry Clean Motor Speed	Electric Load	Extract Speed	Filter Pump Capacity	Base	Filter	Overall Dimensions W x D x H App.	Net.Wt/Shipping Wt. Shipping Size W x D x H App. Shipping Vol.
LEW/DC/15	15 Kg	Ø 700 x 470 D 180 Lts	0.37 KW 35 RPM	1.5 KW	200 RPM	0.37 KW 100 Lts / Min	260 Lts	260 Lts	1000 x 1080 x 1730	475 Kg / 545 Kg 1300 x 1380 x 1930 3.46 M ³
LEW/DC/30	30 Kg	Ø 950 x 500 D 355 Lts	0.75 KW 35 RPM	3.75 KW	200 RPM	0.37 KW 100 Lts / Min	410 Lts	460 Lts	1300 x 1250 x 2000	900 Kg / 115 Kg 1600 x 1500 x 2200 5.45 M ³

NOTE FOR ALL MACHINES :

All dimensions are in mm standard Machine Operate on 415 ± 10% 3 phase, 50Hz AC Electric supply. Specifications Design mentioned above are to Subject to Change without notice:- **** One Complete process may have 2,3, or more also made to as per customer Equipment Specification.**