

Rotary Tiller SUPREMO



Supremo is built to withstand the rigors of commercial jobs. The tiller is designed to go all day after day in the most demanding jobs. Seed bed is prepared within one or two passes and is suitable in removing and mixing residue of maize, wheat, sugarcane etc. which helps to improve soil health. Suitable for hard solid and tend to achieve greater depth penetration resulting in moving and pulverizing more soil.

FEATURES

- Less Maintenance.
- High quality blades.
- Less Diesel Consumption.
- Suitable for Hard Black Cotton Soil.
- Robust Structure.



SPECIFICATIONS

Model No	RTS4MG30	RTS5MG36CG	RTS5MG36	RTS6MG42	RTS6MG48	RTS7MG48	RTS7MG54	RTS8MG54	RTS8MG60	RTS9MG66	RTS5MC36	RTS6MC42	RTS4SG30	RTS5SG36	RTS6SG42	RTS4SC30	RTS5SC36	RTS6SC42
Size (feet)	4	5	5	6	6	7	7	8	8	9	5	6	4	5	6	4	5	6
Gear Box	Multi Speed										Single Speed							
Side Drive	Gear Drive										Chain Drive		Gear Drive		Chain Drive			
Min. Tractor HP Required	30	35	35	45	45	50	50	55	55	75	35	45	30	35	45	30	35	45
Total Width (inch/cm)	59	71	71	78	78	88	88	97	97	111	71	78	59	71	78	59	71	78
Working Width (inch/cm)	49	60	60	68	68	77	77	88	88	101	60	68	49	60	68	49	60	68
Working Depth (inch/cm)	4 inch to 6 inch																	
Working Depth Control	Skids fitted as standard equipment																	
PTO Speed (rpm)	540 / 1000																	
Rotor Speed (rpm)	180-220																	
Weight (Kg.)	440	480	465	495	505	530	540	560	570	610	475	505	425	450	480	430	455	485
Number of Blades	30	36	36	42	48	48	54	54	60	66	36	42	30	36	42	30	36	42

*Company reserves the rights to change/amend products specifications without any prior notice.