

XP-Q600

Thermal Receipt Printer

Key features

- 300mm/s High speed printing
- USB/ Bluetooth interfaces
- Change IP through Web or Serial port
- Support Linux, Win 8.1 system



Windows 7



Windows 8



Windows 10



Linux



Specifications

Model	XP-Q600
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	79.5± 0.5mm
Roll paper	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13 /JAN8 EAN8 /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranII Latvian Arabic PT151 1251
NV FLASH	256K Bytes
Input buffer	64K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Lan+Serial+USB
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.1 kg
Dimension	195× 140× 142.5mm (D× W× H)