

Rotary Tiller **ROBUSTO**



A Robust design and ultimate tillage technology suitable for hard, black cotton and rocky soil. Heavy duty gear box and frame makes it strong for rough and tough conditions. The working depth can be adjusted by the height of the skids, which is easily done with the adjustment bracket on the Rotary Tillers.

FEATURES

- Less Maintenance.
- High quality blades.
- Less Diesel Consumption.
- Suitable for Hard Black Cotton Soil.
- Robust Structure.



SPECIFICATIONS

MODEL	RTH5MG36	RTH6MG42	RTH6MG48	RTH7MG48	RTH7MG54	RTH8MG54	RTH8MG60	RTH9MG66	RTH12MG 84
Size (Feet)	5	6	6	7	7	8	8	9	12
Overall Width (Inch)	72	79	79	89	89	98	98	112	152
Working Width	60	68	68	77	77	88	88	101	140
Weight (kg) Without Side disc	525	555	565	575	585	605	615	685	870
Hitch Type	CAT-II								
Min. HP required	40	50	50	55	55	60	60	75	90
Gear Box	Multi Speed								
Side Transmission	Gear Drive								
Working Depth min/max.	4 Inch - 6 Inch								
Number of Blades	36	42	48	48	54	54	60	66	84
PTO speed (rpm)	540/1000								
Working Depth Control	Skids Fitted as Standard Equipment								
Rotor Speed	180-220								

*Company reserves the rights to change/amend products specifications without any prior notice.