

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE	- °C TO - °C	
	VOLTAGE	250 V AC	OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT		APPLICABLE CABLE	MAX $\phi$ 7.5	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2h FOR 3 DIRECTIONS.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms, AT 3 TIMES FOR 6 DIRECTIONS.		X	-	
ENVIRONMENTAL CHARACTERISTICS					
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
$\Delta$					
REMARK			APPROVED	HO. MIWA	07.01.16
			CHECKED	HO. MIWA	07.01.16
			DESIGNED	SJ. SHIMIZU	07.01.16
Unless otherwise specified, refer to JIS C 5402.			DRAWN	SJ. SHIMIZU	07.01.16
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-027202-01
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	DX-36-CV1	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL230-0056-3-00	$\Delta$ 1/1